




ISO 9001 2015



اصفهان دما
ISFAHAN DAMA

WARM AIR FURNACE



135-1398-6

www.isfahandama.com

info@isfahandama.com

WARM AIR FURNACE

Features:

- No need to central mechanical room and other equipments.
- Take advantage of recent technologies and relative standards.
- Maximized heat transferred and efficiency.
- Body is insulated and made in 3 layers.
- Fan is centrifugal type FC, balanced and quiet operation.
- Suitable to use natural gas or diesel fuel oil burner.
- Indoor or outdoor installation.

Options:

- Air filter is possible to use.
- Room temperature is under control by relative thermostat.

Used in:

Industrial plants, Workshops, Sport Buildings, Poultrys, Green Houses, Banks, Mosques, Dormitories and Public Areas.



MODEL NO.	CAPACITY Kcal/hr × 1000	AIR DELIVERY M ³ /hr	MOTOR KW	DIMENSIONS			WEIGHT kg
				W	L	H	
IDH – 60	60	4800	0.55	77	110	195	220
IDH – 80	80	6400	0.75	85	135	200	355
IDH – 100	100	8000	1.5	85	135	205	370
IDH – 150	150	12000	2.2	93	170	230	556
IDH – 200	200	16000	3	125	170	245	720
IDH – 250	250	20000	4	125	200	255	910
IDH – 300	300	24000	4	125	250	255	1100
IDH – 400	400	27000	4	125	250	280	1340